

# HALF LANTERN

IP44

A traditional wall mounted half lantern.


Classic design Half Lantern in vandal and weather resistant polycarbonate.

The lantern is designed to be fitted near to doorways to optimise illumination for entrance areas, with this location in mind the PIR operates at 6 metres to reduce the number of nuisance activations.

The Half Lantern range is available with energy saving lamps or LED versions.



- Easy to install.
- IP44.
- Choice of standard, photocell and PIR options.
- PIR: Day time walk test.
- Shatter-proof polycarbonate detector.
- PIR range of 6 metres.
- 110° angle of detection.
- Photocell: dusk to dawn sensor.
- Designed to BS EN 60598.



Size	Half Lantern
A	182mm
B	394mm
C	118mm

## Codes

Half Lantern	60W	9W HF	13W HF	18W HF
Black	HL/BK060	HL/BK009E	HL/BK113E	HL/BK118E
White	HL/WK060	HL/WK009E	HL/WK113E	HL/WK118E
Titanium	HL/XK060	HL/XK009E	HL/XK113E	HL/XK118E

Half Lantern PIR	60W PIR	9W HF PIR	13W HF PIR	18W HF PIR
Black	HL/BK060P	HL/BK009EP	HL/BK113EP	HL/BK118EP
White	HL/WK060P	HL/WK009EP	HL/WK113EP	HL/WK118EP
Titanium	HL/XK060P	HL/XK009EP	HL/XK113EP	HL/XK118EP

Half Lantern Photocell	60W PC	9W HF PC	13W HF PC	18W HF PC
Black	HL/BK060C	HL/BK009EC	HL/BK113EC	HL/BK118EC
White	HL/WK060C	HL/WK009EC	HL/WK113EC	HL/WK118EC
Titanium	HL/XK060C	HL/XK009EC	HL/XK113EC	HL/XK118EC