

LTE700 WFAV25 Masthead Amplifier Kit

Article No. 370579

- F-Connector Masthead Amplifier and Power Supply
- 12-25dB Variable Gain
- 1 Input, 1 Output
- Weatherproof Housing
- Fully Screened Enclosure
- Product complies with EN 303 354 (Classification 1)



Enhanced
TRIPLE FILTERING
for
4G, 5G + TETRA

Item Name:		WFAV25
Art No:		370579
Number of Inputs	-	1
Number of Outputs	-	1
Input Frequency Range (MHZ)	MHz	470-694
Output Frequency Range (MHz)	MHz	470-694
Forward Gain (dB Typ)	dB (Typ.)	25±2
Gain Control(dB)	dB	0-13
Rejection 450MHz(dB)	dB	≥12
Gain Reduction 686MHz to 694MHz (dB)	dB	≤4.0
Rejection 703MHz to 738MHz (dB)	dB	≥10
Rejection 738MHz to 960MHz	MHz	≥40
Noise Figure (dB)	dB	≤4.0
Amplifier Intermodulation(dBm)	dBm	≥-4.0
Power In	V / mA	12V/65mA
EAN	-	5061038082685
Comments	-	Product compliant with EN 303 354 standard (Classification 1)
	-	PSU for Indoor Use Only